



ViBa Water. Drink Safe.

Wasserfilter „ViBa CF I“

Art. Nr. 20457

Der Wasserfilter "ViBa CF I" besteht aus einem Kohlefilter auf Kokosnussbasis, der speziell zur Entfernung von Schwermetallen wie Blei und Quecksilber sowie von Medikamentenrückständen und Pestiziden entwickelt wurde. Zusätzlich hat er eine hervorragende Adsorptionsfähigkeit für Chlor und allgemeine organische Verbindungen, was den Geschmack und Geruch des Wassers deutlich verbessert.

Membrantyp:	Kokosnussbasierte Aktivkohle
Maximale Filterporengröße:	5 µm
Aktivkohleabsorption:	Entfernt > 99% aller freien Chlore Beseitigung von - Schwermetallen - Herbizide - Pestizide - medizinische Rückstände - schlechter Geschmack und Geruch
Durchflussmenge:	6 L/min @ 1,5 bar/22 PSI (8 L/min @ 2 bar/29 PSI)
Lebensdauer:	approx. 5.000 ltrs or 4-6 months, depending on water circumstances
Max. Druck:	5 bar (75 psi), optimaler Druck : 1.5 bar (22 PSI)
Max. Temperatur:	40°C (104°F)
Weight:	470 g

Die Standzeit hängt von den örtlichen Wasserbedingungen, der Menge an Mikropartikeln und dem Grad der Vorfiltration ab.

Exclusive Distributor:
Ship Safety Group GmbH & Co. KG
Graf-Zeppelin-Ring 17
27211 Bassum [Germany]

Tel.: +49 4241 – 613 00 41
E-Mail: viba@ship-safety-group.com

Internet: www.viba-water.com



ViBa Water. Drink Safe.

Water filter „ViBa CF I“

Art. No. 20457

The Water filter “ViBa CF I” consists of a coconut based carbon filter, which is specifically designed to remove heavy metals such as lead and mercury, as well as medicine residues and pesticides. Additionally it has an excellent adsorptive capacity for chlorine and general organic compounds greatly improving the taste and odour of the water.

Membrane type:	Coconut based Carbon shell
Filter max. pore size	5 micrometers
Carbon absorption	Reduces > 99% of free chlorine Removal of - heavy metals - herbicides - pesticides - medical residues - bad taste and odor
Flow rate:	6 L/min @ 1.5 bar/22 PSI (8 L/min @ 2 bar/29 PSI)
Service life:	approx. 5.000 ltrs or 4 -6 months, depending on water circumstances
Max. pressure:	5 bar (75 psi), optimal pressure: 1.5 bar (22 PSI)
Max. temp:	40°C (104°F)
Weight:	470 g

Service life depends on local water conditions, the amount of micro particles and level of pre -filtration.

Exclusive Distributor:

Ship Safety Group GmbH & Co. KG
Graf-Zeppelin-Ring 17
27211 Bassum [Germany]

Tel.: +49 4241 – 613 00 41

E-Mail: viba@ship-safety-group.com

Internet: www.viba-water.com